

DSA230i Specifications



Features

- 1-way loudspeaker for voice and BGM applications
- Supplement to DSA250i for increased LF output & pattern control
- Vertical coverage pattern adjustable to fit the audience area
- Integral signal processing and amplification
- Built-in electronic driver protection
- Wall mounting hardware included

Description

The DSA 230i is a unique, column-type loudspeaker for voice-only and voice/BGM (background music) applications. It also functions with additional DSA Series loudspeakers to provide increased performance. For example, used with a DSA250i, the DSA230i extends directivity to and increases the output at lower frequencies.

The DSA230i has the remarkable versatility of a user-adjustable, vertical beamwidth. This is made possible because each transducer has its own DSP (digital signal processing) and power amplifier. Built-in networking provides for remote PC operation and control. Intended to be flat-mounted to a wall, the user directs the DSA230i's output from this position to the desired coverage area using the supplied DSAPilot software. Pattern asymmetry provides similar sound levels to both near and far listeners. Each of the two inputs has user-adjustable EQ, delay, and compression.

DSA loudspeakers are engineered as a solution for applications with difficult acoustics, physical mounting limitations, precise vertical coverage requirements, and difficult aesthetic requirements. They can replace typical horn or column-type loudspeakers in small to medium venues. These include houses of worship, auditoriums, theaters, concert halls, conference rooms, transportation centers, athletic facilities, classrooms, museums, shopping malls, and theme parks. The enclosure profile and appearance reduces architectural impact.

Warranty: five years loudspeaker components; two years electronics.

COMPLIANCES



EN 60065:2002, EN 55103-1:1997, EN 55103-2:1997, EN55103-1, EN55103-2, EN60065



1-WAY DIGITALLY STEERABLE ARRAY

See TABULAR DATA notes for details

CONFIGURATION

Subsystem	Transducer	Loading
LF	8x 4 in cone	Direct radiating
Operating Mode	Amplifier Channels	External Signal Proc.
Self-powered	8x high efficiency	None

ACOUSTICAL PERFORMANCE

Operating Range	78 Hz to 10 kHz	
Nominal Beawidth	Horz	120°
	Vert	Digitally variable

ELECTRONIC PERFORMANCE

Analog		
Amplifier Output (ea)	28.3 V	50 W @ 16 ohm
Input (Audio A and B):		
Configuration	Balanced differential	
Nominal Sensitivity	0.9 V / 1.25 dBu	For full output
Maximum Signal	12.2 V / 24 dBu	
Input Routing	A + B, A or B, priority B over A	
Digital		
A to D/ D to A	48 kHz, 24 bit	
Processor	32 bit dual SHARC (Super Harvard Architecture Computer)	
Propagation Time	4.3 ms	

INPUT SIGNAL PROCESSING

Filters	Frequency	Boost/Cut	Q
Parametric	10 to 24000 Hz	+15/-15 dB	0.25 to 64
6 or 12 dB Lo Shelf	10 to 24000 Hz	+15/-15 dB	
6 or 12 dB Hi Shelf	10 to 24000 Hz	+15/-15 dB	
HPF and LPF	10 to 24000 Hz	12/18/24 dB/oct	L-R, BW, Bessel
Compression			
Threshold	-40 to +24 dBu		
Ratio	1.2:1 to inf:1		
Attack (ms)	slow (64)/med (16)/fast (2)		
Release (ms)	slow (256)/med (64)/fast (8)		

Gain	-40 dB to +10 dB		
Mute	on/off		
Signal Delay	300 ms maximum		
Meters			
Input	-40 to +20 dBu		
Output	-30 to 0 dB	ref 0 dB = full output	
Gain Reduction	0 dB to -60 dB (compression)		

CONNECTIONS

Computer Network	
Standard	EIA-485
Optional	CobraNet (requires EAW CM-1 Interface Card accessory)
Fault Supervision	
	Form C dry contact relay

AC Mains	Voltage / Frequency	Maximum Current
DSA230i (115 V)	100 to 120 V / 50 to 60 Hz	4 A
DSA230i (230 V)	220 to 240 V / 50 to 60 Hz	4 A


ORDERING DATA

Description	Part Number
DSA230i White 115 V	0015159-00
DSA230i White 230 V	0015159-01
Optional Accessories	
CM-1 CobraNet Interface Card	0005987
DSA Fly-Bar Kit	0007445
DSA Enclosure Connecting Kit	0007446

DSA230i Specifications

ENCLOSURE


Material Rear: extruded aluminum, Front baffle: PVC
 Finish Powder-coated white
 Grille Powder-coated perforated steel



NOTE: This drawing has been reduced. Do not scale.

DSA230i Specifications

DSA230i 1/3 OCTAVE POLAR RESPONSES: 40° Vertical Beamwidth




Referenced to 20 m, 1/3 octave smoothing, 5° resolution, 1 dB / division


NOTE: The DSA230i's acoustical performance varies with the steering and beamwidth settings as well as whether it is used singly or in clusters with other DSAi loudspeakers. The above graphs are only an example of the wide range of steering possibilities.

DSA230i Specifications

INPUT PANEL



SIGNAL DIAGRAM



LEGEND

- DSP:** Digital Signal Processing for EQ, limiting, and delay.
- LF/MF/HF:** Low Frequency / Mid Frequency / High Frequency.
- PWR AMP:** Power Amplifier.
- Σ:** Summing Amplifier

NOTES

TABULAR DATA


1. **Measurement/Data Processing Systems:** Primary - FChart: proprietary EAW software; Secondary - Brüel & Kjær 2012.
2. **Microphone Systems:** Earthworks M30; Brüel & Kjær 4133
3. **Measurements:** Dual channel FFT; length: 32 768 samples; sample rate: 48 kHz; logarithmic sine wave sweep.
4. **Measurement System Qualification** (includes all uncertainties): SPL: accuracy +/-0.2 dB @ 1 kHz, precision +/-0.5 dB 20 Hz to 20 kHz, resolution 0.05 dB; Frequency: accuracy +/-1 %, precision +/-0.1 Hz, resolution the larger of 1.5 Hz or 1/48 octave; Time: accuracy +/-10.4 μs, precision +/-0.5 μs, resolution 10.4 μs; Angular: accuracy +/-1°, precision +/-0.5°, resolution 0.5°.
5. **Environment:** Measurements time-widowed and processed to eliminate room effects, approximating an anechoic environment. Data processed as anechoic or fractional space, as noted.
6. **Measurement Distance:** 7.46 m. Acoustic responses represent complex summation of the subsystems at 20 m. SPL is referenced to other distances using the Inverse Square Law.
7. **Enclosure Orientation:** For beamwidth and polar specifications, as shown in Mechanical Specification drawing.
8. **Volts:** Measured rms value of the test signal.
9. **Watts:** Per audio industry practice, "loudspeaker watts" are calculated as voltage squared divided by rated nominal impedance. Thus, these are not True Watt units of energy as defined by International Standard.
10. **SPL:** (Sound Pressure Level) Equivalent to the average level of a signal referenced to 0 dB SPL = 20 microPascals.
11. **Subsystem:** This lists the transducer(s) and their acoustic loading for each passband. Sub = Subwoofer, LF = Low Frequency, MF = Mid Frequency, HF = High Frequency.
12. **Operating Mode:** User selectable configurations. Between system elements, a comma (,) = separate amplifier channels; a slash (/) = single amplifier channel. DSP = Digital Signal Processor. **IMPORTANT:** To achieve the specified performance, the listed external signal processing must be used with EAW-provided settings.
13. **Operating Range:** Range where the processed Frequency Response stays within -10 dB SPL of the power averaged SPL within this range; measured on the geometric axis. Narrow band dips are excepted.
14. **Nominal Beamwidth:** Design angle for the -6 dB SPL points, referenced to 0 dB SPL as the highest level.
15. **Axial Sensitivity:** Power averaged SPL over the Operating Range with an input voltage that would produce 1 W at the nominal impedance; measured with no external processing on the geometric axis, referenced to 1 m.
16. **Nominal Impedance:** Selected 4, 8, or 16 ohm resistance such that the minimum impedance point is no more than 20% below this resistance over the Operating Range.
17. **Accelerated Life Test:** Maximum test input voltage applied with an EIA-426B defined spectrum; measured with recommended signal processing and Recommended Protection Filter.
18. **Calculated Axial Output Limit:** Highest average and peak SPLs possible during the Accelerated Life Test. The Peak SPL represents the 2:1 (6 dB) crest factor of the Life Test signal.
19. **High Pass Filter:** This helps protect the loudspeaker from excessive input signal levels at frequencies below the Operating Range.

GRAPHIC DATA

1. **Resolution:** To remove insignificant fine details, 1/12 octave cepstral smoothing was applied to acoustic frequency responses and 1/3 octave cepstral smoothing was applied to the beamwidth and impedance data. Other graphs are plotted using raw data.
2. **Frequency Responses:** Variation in acoustic output level with frequency for a constant input signal. Processed: normalized to 0 dB SPL. Unprocessed inputs: 2 V (4 ohm nominal impedance), 2.83 V (8 ohm nominal impedance), or 4 V (16 ohm nominal impedance) referenced to a distance of 1 m.
3. **Processor Response:** The variation in output level with frequency for a constant input signal of 0.775 V = 0 dB reference.
4. **Beamwidth:** Average angle for each 1/3 octave frequency band where, starting from the rear of the loudspeaker, the output first reaches -6 dB SPL referenced to 0 dB SPL as the highest level. This method means the output may drop below -6 dB SPL within the beamwidth angle.
5. **Impedance:** Variation in impedance magnitude, in ohms, with frequency without regard to voltage/current phase. This means the impedance values may not be used to calculate True Watts (see 9 above).
6. **Polar Data:** Horizontal and vertical polar responses for each 1/3 octave frequency band 100 Hz to 16 kHz or Operating Range.

DSA 230i Specifications

DSA SERIES PERFORMANCE MATRIX

Cluster	 DSA230i	 DSA250i	 DSA230i / DSA250i	 DSA230i / DSA230i / DSA250i
Height (in/mm)	36.5/927	50.8/1290	87.6/2224	124.3/3158
Width (in/mm)	9.3/237	9.3/237	9.3/237	9.3/237
Depth (in/mm)	9.3/237	9.3/237	9.3/237	9.3/237
Weight (in/mm)	62/28.1	84/38.1	146/66.2	208/94.3
<hr/>				
Nominal Horizontal Beamwidth	120	120	120	120
Beamwidth Range	800 Hz to 4.5 kHz	800 Hz to 10 kHz	800 Hz to 10 kHz	800 Hz to 10 kHz
20° NOMINAL VERTICAL BEAMWIDTH				
Beamwidth Range	1 kHz to 8 kHz	1 kHz to 15 kHz	400 Hz to 15 kHz	270 Hz to 15 kHz
Frequency Range (+/- 3 dB tolerance)	90 Hz to 6.5 kHz	90 Hz to 13 kHz	90 Hz to 13 kHz	90 Hz to 13 kHz
Operating Range (-10 dB frequencies)	78 Hz to 10 kHz	78 Hz to 15 kHz	78 Hz to 15 kHz	78 Hz to 15 kHz
SPL Limit (avg)	116.0	117.2	123.4	126.5
SPL Limit (peak)	122.0	123.2	129.4	132.5
40° NOMINAL VERTICAL BEAMWIDTH				
Beamwidth Range	500 Hz to 10 kHz	500 Hz to 15 kHz	200 Hz to 15 kHz	130 Hz to 15 kHz
Frequency Range (+/- 3 dB tolerance)	90 Hz to 6.5 kHz	90 Hz to 13 kHz	90 Hz to 13 kHz	90 Hz to 13 kHz
Operating Range (-10 dB frequencies)	78 Hz to 10 kHz	78 Hz to 15 kHz	78 Hz to 15 kHz	78 Hz to 15 kHz
SPL Limit (avg)	115.6	116.2	121.7	124.1
SPL Limit (peak)	121.6	122.2	127.7	130.1
60° NOMINAL VERTICAL BEAMWIDTH				
Beamwidth Range	300 Hz to 10 kHz	300 Hz to 15 kHz	135 Hz to 10 kHz	90 Hz to 10 kHz
Frequency Range (+/- 3 dB tolerance)	90 Hz to 8.2 kHz	90 Hz to 13 kHz	90 Hz to 10 kHz	90 Hz to 13 kHz
Operating Range (-10 dB frequencies)	78 Hz to 10 kHz	78 Hz 15 kHz	78 Hz to 15 kHz	78 Hz to 15 kHz
SPL Limit (avg)	114.2	115.5	119.9	120.8
SPL Limit (peak)	120.2	121.5	125.9	126.8
80° NOMINAL VERTICAL BEAMWIDTH				
Beamwidth Range	225 Hz to 5.5 kHz	225 Hz to 10 kHz	110 Hz to 10 kHz	80 Hz to 10 kHz
Frequency Range (+/- 3 dB tolerance)	90 Hz to 8.2 kHz	90 Hz to 13 kHz	90 Hz to 13 kHz	90 Hz to 13 kHz
Operating Range (-10 dB frequencies)	78 Hz to 10 kHz	78 Hz to 15 kHz	78 Hz to 15 kHz	78 Hz to 15 kHz
SPL Limit (avg)	113.1	114.1	118.3	119.7
SPL Limit (peak)	119.1	120.1	124.3	125.7

NOTES

1. Beamwidth and Frequency data is referenced to 20 m on axis, including air losses; steering at 0 degrees.
2. Beamwidth Range is where the pattern widens to more than 1.5 times nominal below the low frequency and narrows to less than 0.67 times nominal above the high frequency.
3. Avg SPL Limits are referenced to 1 m at an output equivalent to 0.5 times rated amplifier power at nominal impedance.
4. Peak SPL Limits are reference to 1 m at an output equivalent to maximum peak amplifier power at nominal impedance.