

CRYSTAL2-R TIME-ALIGN®

APPLICATIONS

Portable Sound Reinforcement Theatrical Sound Reinforcement
Portable DJ Systems

DESCRIPTION

The CRYSTAL2-R is a full range, long throw loudspeaker system offering high fidelity, high efficiency and high power handling capacity. It is designed for applications where high sound pressure and highly directive long throw capability are required. The CRYSTAL2-R includes protective end caps, handles, a stand adapter, and quick-release rigging attachment points. Constructed from 15mm 13-ply birch plywood with a black Ro Tex™ finish, leaves the enclosure durable and attractive.



SPECIFICATIONS

System Type:

2-way vented 2.5 ft³

Enclosure:

15 mm 13-ply birch plywood
horizontally arrayable

Finish:

Black Ro Tex™ True water born environmental
finish

Grille:

14 Gauge black powder coated perforated
steel in a welded extruded aluminum frame

Low Frequency Components:

2 - E-12 12" Transducers, 2.5" Voice coil,
80 oz. Magnet

High Frequency Components:

Transducer, 1.4" Exit compression driver,
3" Titanium diaphragm, Elliptic conical
waveguide

Input Connector:

Dual Neutrik® speakON

Hardware:

2 - Recessed handles
35 mm Stand adapter
2 - Birch skid plates with protective
UHMW polyethylene bumpers
Optional Crystal-F1 or Crystal-F2 rigging kit for
flying multiple cabinet arrays

Fly Points Safe Working Load:

200 lbs Upper most rigging points

Crossover Type:

Passive Time-Align® equalizer type @ 1.9 kHz

Time Offset Between Driver:

< ± 25 Microseconds

Sensitivity:

103 dB SPL (2.83 V @ 1m)

Frequency Response:

80 Hz to 18 kHz ±3 dB

Low Frequency Limit:

80 Hz

Maximum Calculated Continuous Acoustic Output:

130 dB SPL @ 1m

Power Handling:

2000 W continuous (IEC 60268)

Recommended Amplifier Power:

1500 to 3000 W at rated impedance

Rated Impedance:

8 Ohms

Coverage Pattern:

55 degrees Horizontal (-6 dB)
40 degrees Vertical (-6 dB)

Recommended High Pass Filter:

60 Hz

Polarity:

A positive asymmetrical signal applied to the +
terminal will result in a positive asymmetrical
acoustical pressure

Dimensions:

39.5" h x 14.5" w x 17" d
101 cm x 37 cm x 44 cm

Weight:

110 lbs
50 kg

Custom Finishes:

Optional custom finishes include white,
unfinished ready to paint and outdoor weather
treatment.

TIME-ALIGN®, TIME-ALIGNED™ and TIME-ALIGNMENT™ are trademarks of E.M. Long Associates.
BAG END® is a registered trademark of Bag End, Inc.

CRYSTAL2-R TIME-ALIGN®

ABOUT TIME-ALIGN® TECHNOLOGY

Time-Align® assures that the fundamental and overtones of a complex, transient, acoustical signal are presented to the listener in the same relationship as the electrical signal at the input terminals of the loudspeaker. The conventional loudspeaker spreads out the sound in time. When a rapid series of transients occur the results are blurring and lost detail. With Time-Align®, a transient is presented as a tight package of energy, with the same time relationships as the natural sound. This means that a rapid series of transients will be heard clearly.



True Time-Alignment™ requires much more than just physically lining up the loudspeaker components. It requires consideration of the driver placement, driver delay and adjustment of the crossover delay parameters. This achieves the precise simultaneous acoustical arrival time of each driver throughout the crossover region.

The first Time-Aligned™ Loudspeaker was invented by EM Long Associates in 1976 utilizing the Time-Align® generator invented and built by Ronald Wickersham. In 1980 Bag End® incorporated Time-Align® technology into our full range loudspeaker systems. Along with state-of-the-art laboratory instruments, the proprietary Time-Align® generator is still in use today to verify the time domain performance of our loudspeaker systems. When comparing a genuine Bag End® Time-Aligned™ loudspeaker system to any other, our technology and design is easy to hear and appreciate. The dramatic clarity, realism, and overall pleasant sound of our Time-Aligned™ systems are well noted worldwide.

ABOUT OUR RO TEX™ FINISH

The durable Ro Tex™ finish is double layered on Bag End™ "R" series or Road cabinets. And single layered on installation or "I" cabinets. Ro Tex™ is a water born

environmentally safe finish. It's uniquely strong and long lasting. As it solidifies it attaches and bonds to the wooden cabinet to make a super hard and durable permanent finish. Its light texture offers an attractive and rugged finished look

ABOUT BAG END® LOUSPEAKERS

Bag End loudspeakers began in 1976 in a small shop by people dedicated to the pursuit of making high quality loudspeaker systems. Over the decades Bag End® has employed the very best construction techniques and innovative acoustical designs into their products. The ground breaking introductions of the Time-Align® and ELF™ Technologies into sound reinforcement and studio monitor loudspeakers in the 1980's was followed by Minima One™ self-powered systems and the highly unique E-Trap™, electronic bass trap. Over the decades, Bag End® has been a leader in providing uniquely good sounding products and extraordinary service to our customers world wide.

DIMENSIONS

