

# S15-I V-BASS

## APPLICATIONS

Restaurant Foreground Systems      Nightclub Installations  
Fitness Centers                              Low Frequency Special Effects  
Discotheque Subwoofer                  House of Worship

## DESCRIPTION

The S15-I is a high output low frequency loudspeaker system designed to provide high fidelity low frequency extension to an audio reproduction system. The S15-I incorporates our proprietary tuned, damped, V-BASS alignment, providing greater output and low distortion. Artifacts and vent turbulence, even at extreme levels, are reduced. This makes the S15-I an ideal choice for high level systems requiring stability and reliability under the most demanding long term use. Designed for permanent installations the S15-I is constructed from multi laminated hardwood plywood and features a durable attractive black Ro Tex™ finish, steel grille and Integral Fly points.



## SPECIFICATIONS

### System Type:

Vented system 2.9 ft<sup>3</sup>

### Enclosure:

3/4" 13-ply solid hardwood core plywood

### Finish:

Black Ro Tex™ True water born environmental finish

### Grille:

16 Gauge black power coated perforated steel

### Low Frequency Components:

E-15 Transducers, 15" Cone, 2.5" Voice coil, 80oz Magnet

### Input Connector:

Cinch 142 screw terminal barrier strip

### Hardware:

Flypoints  
Forged steel eye bolts

### Fly Points Safe Working Load:

F4 rigging points  
200 lbs Upper most points

### Crossover Type:

Requires Low Pass

### Sensitivity:

99 dB SPL (2.83 V @ 1m)

### Frequency Response:

40 Hz to 150Hz

### Low Frequency Limit:

32 Hz (-10dB)

### Maximum Calculated Continuous Acoustic Output:

126 dBSPL @ 1m

### Power Handling:

300 W continuous (IEC)  
600 W program

### Recommended Amplifier Power:

300 to 600 W at rated impedance

### Rated Impedance:

8 Ohms

### Polarity:

A positive asymmetrical signal applied to the + terminal will result in a positive asymmetrical acoustical pressure

### Dimensions:

28"h x 18"w x 15"d  
72 cm x 46 cm x 39 cm

### Weight:

54 lbs  
24kg

### Custom Finishes:

Optional custom finishes include white, unfinished ready to paint and outdoor weather treatment.

BAG END® is a registered trademark of Bag End, Inc.

# S15-I V-BASS

---

## ABOUT OUR RO TEX™ FINISH

The durable Ro Tex™ finish is double layered on Bag End™ “R” series or Road cabinets. And single layered on installation or “I” cabinets. Ro Tex™ is a water born environmentally safe finish. It's uniquely strong and long lasting. As it solidifies it attaches and bonds to the wooden cabinet to make a super hard and durable permanent finish. Its light texture offers an attractive and rugged finished look

## ABOUT BAG END® LOUDSPEAKERS

Bag End loudspeakers began in 1976 in a small shop by people dedicated to the pursuit of making high quality loudspeaker systems. Over the decades Bag End® has employed the very best construction techniques and innovative acoustical designs into their products. The ground breaking introductions of the Time-Align® and ELF™ Technologies into sound reinforcement and studio monitor loudspeakers in the 1980's was followed by Minima One™ self-powered systems and the highly unique E-Trap™, electronic bass trap. Over the decades, Bag End® has been a leader in providing uniquely good sounding products and extraordinary service to our customers world wide.

---

## DIMENSIONS

