

DATA SHEET

VOCIA® WS-10

WALL PAGING STATION



The WS-10 is a wall-mounted networked paging station for use in Vocola® systems. The WS-10 features embedded DSP and on-board memory to support standard and advanced public address functionalities. The WS-10 can store 999 user-configurable page codes. Additionally, all device-specific configuration information is stored locally, which means the WS-10 does not rely on a centralized controller for processing and page routing. Thus, the processing, routing and storage functionality in a Vocola system is decentralized, which eliminates any centralized point of failure. As part of the Vocola system, the WS-10 meets paging requirements for facilities of all sizes.

FEATURES

- Push-to-talk button with status indication
- Up to 999 user-configurable page codes
- Four software configurable non-emergency priority paging levels
- Local digital signal processing, including gain, filters, and compressor/limiter
- Local storage of configuration data
- Local storage of default and/or custom preambles
- Built-in store and forward functionality
- CobraNet® audio/control with dynamic use of available bundles, plus power over single Ethernet cable
- Backlit liquid crystal display (LCD) technology
- Optional PIN to restrict unauthorized use
- Auxiliary Port provides connection for power, line-level audio, and bi-directional RS232 for transmitting Vocola Text Protocol (VTP) commands
- High-quality, noise-cancelling handheld microphone
- Sturdy, surface-mounted component housing
- Rotary ID switches for unit identification
- CE marked and RoHS compliant
- Covered by Biamp Systems' 5-year warranty

ARCHITECTS & ENGINEERS SPECIFICATION

The wall-mounted paging station shall be designed exclusively for use with Biamp® Vocolta® systems. The wall-mounted paging station shall provide paging audio and control data via CobraNet®, and receive Power over Ethernet (PoE), utilizing a single (CAT5) network cable to a rear panel RJ-45 connector. Ten buttons shall be provided on the front panel for recalling page codes with preambles. Multiple wall-mounted paging stations may be connected to a Vocolta system by means of Ethernet switches. Four software configurable non-emergency priority paging levels shall be available. The wall mounted paging station shall include page priority override, store and forward, and lock-out capabilities. Each wall-mounted paging station shall provide local digital audio signal processing, local storage of configuration data, and preambles. Wall-mounted paging stations shall possess a backlit LCD screen, PIN code accessibility, and a high-quality, noise-cancelling handheld microphone. The wall-mounted paging station shall be CE marked and shall be compliant with the RoHS directive. Warranty shall be five years. The wall-mounted paging station shall be a Vocolta WS-10.

VOCIA WS-10 SPECIFICATIONS

| | | | |
|--|--|---|--|
| Network Connection: | RJ-45 with shielded Ethernet (CAT5, CAT5e, CAT6 or CAT7) | Power: | |
| Frequency Response (100Hz ~ 20kHz): | +0, -1dB | PoE: | 802.3af Class 2 |
| THD+N (100Hz ~ 8kHz): | <0.05% | Aux: | 24V DC 6W |
| Effective Input Headroom: | 30dB | Overall Dimensions (excl. microphone): | |
| System Headroom: | 18dB | Height: | 5.3 inches (135 mm) |
| Gain: | Adjustable in 1dB steps over a 30dB range | Width: | 11.9 inches (302 mm) |
| Maximum Input: | 125dB SPL | Depth: | 1.9 inches (48 mm) |
| Mic Type: | Noise cancelling dynamic microphone with dual transducer (monitored) | Weight: | 2.6 lbs (1.2 kg) |
| Mic Pattern: | Cardioid | Mic Cord Length (extended): | 4 ft. (1219 mm) |
| Mic Frequency Response: | 100Hz-10kHz | Environment: | |
| Auxiliary Port: | | Ambient Operating Temperature Range: | 23-104° F (-5 - 40° C) |
| PTT: | Switch contact between pin and ground | Humidity: | 0 - 95% non-condensing |
| 12V DC Out: | 50mA | Altitude: | 0-10,000 Feet (0-3000 Meters) MSL |
| RS-232: | 57600 kbps | Sample Rate: | 48kHz |
| Balanced Line In: | -10dB Nominal | A/D Converters: | 24-bit |
| Input Impedance: | 3kΩ | Compliance: | |
| | | | CE marked (Europe) UL and C-UL listed (USA and Canada) RoHS Directive (Europe) RINA (Italy) |

VOCIA WS-10 WALL-MOUNTING BRACKETS

