

Xs118

Band-Pass Subwoofer



- Compact band-pass sub-bass
- Long excursion 18"/100mm VC speaker
- Extended low end roll-off
- Top hat fitting for pole mounting X12/X15

OVERVIEW

The Xs118 is a 1400W compact, powerful subwoofer system loaded by a long excursion, European made, 18inch neodymium woofer.

This professional true sub-bass Band-pass system was engineered for high-level, extended low frequency output.

The Xs118 is also equipped with a top-mounted pole socket that, when in ground stacked applications, can be used to mount satellite speakers equipped with standard 35mm pole sockets.

Quality construction features include CNC-machined 18mm Baltic birch plywood enclosures, heavily braced and coated in wear resistant textured black paint, heavy-duty power-coated steel grilles and Neutrik NL4 connectors.

TECHNICAL SPECIFICATIONS

Technical Data	
Speaker Type:	Passive Band-Pass Subwoofer
Acoustical Data	
Frequency Response (-6dB):	36Hz - 200Hz
Low Frequency Extension (-10dB):	31Hz
Sensitivity (1W@1m):	102dB (Half-space)
Calculated Max. SPL (Cont/Peak):	136dB/142dB
Drivers	
Loudspeakers:	1 x 18" (460mm)/4" (100mm) VC, long excursion B&C custom speaker
Electrical Data	
Program/Peak Power:	1400W/2800W (10ms)
Nominal Impedance:	8
Recommended Amplifier:	MA6000 / MA2300 (Bridge)
Recommended Amplifier:	MA3200, MA3800, MA6000
Recommended High-Pass Filter:	30Hz, 18dB/oct Butterworth
Connectors:	2 x Neutrik NL4 parallel wired
Enclosure	
Construction:	Braced 18mm multi-laminate birch ply
Finish:	Textured black semi-matte coating
Protective grill:	Black perforated steel
Fittings:	One 35mm pole mount socket
Handles:	2 on each side
Dimensions (WxHxD):	677 x 560 x 786 mm
Net Weight:	58.3 kg