



Point 15

The Point 15 is the largest enclosure of the Point Series range. It bridges the gap between high power and high fidelity, and should be the choice where high SPL and strong low mid power are a must. The Point 15 will be right at home with live bands of all genres, DJs and high level replay systems.

The Point 15 is available in passive and active(bi-amped) versions. This 15" driver is identical to the driver used in the popular M15 and M215 - Adamson's M Series of stage monitors and drum-fill enclosures. The ND15-L is powerful enough to provide monitoring for performers at a 100,000 person outdoor rock show, it can without a doubt keep up with everything one might need to do in most indoor venues, be it as the main system or as a fill box in large sized venues. The Adamson ND15-L (8 Ω) Kevlar Neodymium driver and the 1.4" exit (16Ω) HF driver mounted on an Adamson fiberglass waveguide, give this powerful loudspeaker coherency and musicality that is unparalleled.

Specifications

Frequency Range (+/- 3dB)	55 Hz - 18 kHz
Nominal Directivity (-6dB) H x V	60° x 40°, 90° x 60° or 40° x 20° Rotatable
Maximum Peak SPL (Active / Passive)**	136 dB / 134.8 dB
Components LF	ND15-L Kevlar Neodymium Driver
Components HF	B&C DE800 3" Diaphragm / 1.4" Exit Compression Driver
Nominal Impedance LF	8 Ω
Nominal Impedance HF	16 Ω
Nominal Impedance Passive	8 Ω
Power Handling (AES / Peak) LF	500 / 2000 W
Power Handling (AES / Peak) HF	110 / 440 W
Power Handling (AES / Peak) Passive	610 / 2440 W
Rigging	4x SLR™ Socket, Built-in Polemount Socket
Connection	2x Speakon™ NL4 (Barrier Strip Optional)
Height Front (mm / in)	726 / 28.63
Width (mm / in)	451 / 17.75
Depth (mm / in)	334 / 13.13
Weight (kg / lbs)	24.8 / 54.5 Active, 26.6 / 58.5 Passive
Processing	Lake, IPD, XTA

**12 dB crest factor pink noise at 1m, free field, using specified processing and amplification

