



A218

Adamson's new A218 houses 2 ND18-S Kevlar Neodymium Sub-Bass drivers in a Front-Loaded Baltic Birch cabinet. The sub is designed to be multi-purpose, and can provide low extension for many of our compact systems, such as the SpekTrix™, Metrix™ or Point Series.™

As with many of our other subwoofers, the A218 has two connection points (NL4) on both the front and the back of the cabinet, making cardioid setup easy and clean looking.

An optional Caster/Cover Kit is available for the cabinet to aid in moving and protecting the sub.

Specifications

Frequency Range (+/- 3dB)	40Hz - 160Hz
Maximum Peak SPL **	138.4 dB
Components LF	2x ND18-S 18" Kevlar Neodymium Drivers
Nominal Impedance LF	4.5 Ω
Power Handling (AES / Peak) LF	2x 800 / 2x 3200 W
Connection	4x Neutrik Speakon™ NL4: 2x Front (Pins 2 +/-), 2x Rear (Pins 1 +/-)
Height Front (mm / in)	584 / 23
Width (mm / in)	1066 / 42
Depth (mm / in)	825 / 32.5
Weight (kg / lbs)	65 / 142
Supported Processing	Lake

**12 dB crest factor pink noise at 1m, half space, using specified processing and amplification

