



PC 5

The Point Concentric 5 is a compact, passive 2-way coaxial loudspeaker, with a 70° conical dispersion pattern. The enclosure is designed to produce linear, high-resolution audio throughout the intended bandwidth. Even though it is of modest size, the PC 5 packs an incredible amount of warmth and punch. The PC5 has two M10 fly points and one Omni Mount 20 series mounting point.

As a stand-alone or fill speaker in distributed systems, the Point Concentric 5 will fit a variety of applications.

All Point Concentric enclosures are constructed of 12 mm Baltic Birch, rather than moulded plastic or fiberglass, resulting in a lower resonant frequency.

Specifications

Frequency Range (-10 dB)	72 Hz - 18 kHz
Nominal Directivity (-6 dB) H x V	70° x 70°
Maximum Peak SPL **	128 dB
Components LF	B&C ALT0050158 5" Driver
Components MF / HF	B&C 5FCX44 5" Coaxial Driver
Nominal Impedance Passive	4 Ω
Power Handling (AES / Peak) LF	100 / 400 W
Power Handling (AES / Peak) MF	100 / 400 W
Power Handling (AES / Peak) HF	10 / 40 W
Power Handling (AES / Peak) Passive	210 / 840 W
Rigging	2x Mini SLR™ Socket (M10), Omni Mount 20 Series with 1/4 - 20 Screws
Connection	2x Speakon™ NL4
Height Front (mm / in)	321 / 12.65
Width (mm / in)	171 / 6.75
Depth (mm / in)	172 / 6.76
Weight (kg / lbs)	5.9 / 13
Processing	Lake, IPD

**12 dB crest factor pink noise at 1m, free field, using specified processing and amplification

